

Secoroc Rock Drilling Tools

Secoroc surface rock drills



Sustainable Productivity

Atlas Copco

Productive, reliable and economic for your application

The Secoroc surface rock drills are suitable for all kinds of surface drilling. They are easy to use, reliable, and can work with low air pressures from 4 bar upwards. An in-line lubricator is included in the delivery of Y19A rock drill.

Y26 has a built-in lubricator. Both type of rock drills are delivered as sinkers with air flushing, but can be converted to water flushing.

When a light sinker is needed, the Y19A is the perfect choice for light construction, light quarrying and secondary blasting. Underground it can be used together with pusher leg FT100.

The Y26 is a sinker suitable for production work in quarries and for general construction applications.



Surface rock drills general specifications		
Product name	Y19A	Y26
Product No.	96000007	96000008
Product code	964G-0-3312300308	964H-0-3312300309
Weight	19 kg	26 kg
Air requirement at 5 bar,	43 l/s	50 l/s
Length incl. drill-steel retainer	600 mm	650 mm
Drill-steel chuck (hex)	22 x 108 mm	22(25) x 108 mm
Hole range diameter	32-42 mm	32-42 mm
Piston bore diameter	65 mm	65 mm
Piston stroke	54 mm	70 mm
Impact frequency at 5 bar	35 l/s	27 l/s
Rotation speed	200 r/min	280 r/min
Hose connection	19 mm	19 mm